

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BUF AQUA STOP 250ML
Identification number : 61757

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Care product / Polish

1.3 Details of the supplier of the safety data sheet

Company : Bergal, Nico & Solitaire Vertr. GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196404
Telefax : +4961319642515
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person
Contact person : Product development / product safety

1.4 Emergency telephone number

+49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

Acute aquatic toxicity, Category 1 H400: Very toxic to aquatic life.

Chronic aquatic toxicity, Category 1 H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

Hazard pictograms



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

: P102 Keep out of reach of children.
Prevention:
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
Response:
 P312 Call a POISON CENTER/doctor if you feel unwell.
Storage:
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
 octane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
 Warning! Container under pressure.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

octane	540-84-1 208-759-1	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 60 - < 70
ethyl acetate	141-78-6 205-500-4	Flam. Liq. 2; H225 STOT SE 3; H336 Eye Irrit. 2; H319 EUH066	>= 2 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Protect unharmed eye.
If easy to do, remove contact lens, if worn.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Irritation
- Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : For specialist advice physicians should contact the Poisons Information Service.

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations.
Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Do not spray on a naked flame or any incandescent material. Take measures to prevent the build up of electrostatic charge.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Store in cool place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. Store at room temperature in the original container.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Care product / Polish

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : not required under normal use

Hand protection

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

- Material** : not required under normal use
- For prolonged or repeated contact use protective gloves.
Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374-1: 2003 (0,4 mm).
- Remarks** : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
- Skin and body protection : not required under normal use
- Respiratory protection : Ensure adequate ventilation, especially in confined areas.
In case of insufficient ventilation, wear suitable respiratory equipment.
Recommended Filter type:
ABEK-P3-filter
- Environmental exposure controls**
- General advice** : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : aerosol
- Colour : colourless
- Odour : characteristic
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/range : No data available
- Boiling point/boiling range : No data available
- Flash point : -60 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : Extremely flammable aerosol.
- Burning rate : No data available
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

Relative density : No data available
Density : 0,656 g/cm³ at 20 °C

Water solubility : No data available
Solubility in other solvents : No data available
Partition coefficient: n-octanol/water : No data available
Ignition temperature : No data available
Thermal decomposition : No data available
Viscosity, dynamic : No data available
Viscosity, kinematic : No data available
Explosive properties : No data available
Oxidizing properties : No data available

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions., No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions., No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.
Other information : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

- Skin corrosion/irritation : May cause skin irritation and/or dermatitis.
- Serious eye damage/eye irritation : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.
- Respiratory or skin sensitisation : No data available
- Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

octane

540-84-1:

Acute oral toxicity : LD50 Oral Rat: > 2.000 mg/kg

Acute inhalation toxicity : LC50 Rat: 0,0242 mg/l
Exposure time: 4 h

ethyl acetate

141-78-6:

Acute oral toxicity : LD50 Rat: 5,62 g/kg

LD50 Rabbit: 4.900 mg/kg

Acute inhalation toxicity : LC50 Rat: 5,900 mg/l
Exposure time: 8 h

Acute dermal toxicity : LD50 Rabbit: > 18 g/kg

LD50 Rabbit: 4.935 mg/kg

SECTION 12: Ecological information

12.1 Toxicity

Components:

octane

540-84-1:

Toxicity to fish : LC0 (Salmo salar (Atlantic salmon)): 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,38 mg/l
Exposure time: 48 h

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 0,72 mg/l

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

ethyl acetate

141-78-6:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 230 mg/l
Exposure time: 96 h
Test Type: flow-through test
- LC50 (Danio rerio (zebra fish)): 430 mg/l
Exposure time: 96 h
Test Type: static test
- LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l
Exposure time: 96 h
Test Type: semi-static test
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 717 mg/l
Exposure time: 48 h
- Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 3.300 mg/l
Exposure time: 48 h
Test Type: Cell multiplication inhibition test
- Toxicity to bacteria : EC0 (Pseudomonas putida): 650 mg/l
Exposure time: 16 h
Test Type: Growth inhibition

12.2 Persistence and degradability

Components:

octane

540-84-1:

- Biodegradability : Result: Not readily biodegradable.
- ThOD : 3,50 g/g

ethyl acetate

141-78-6:

- Biodegradability : Result: Readily biodegradable
Biodegradation: 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301

12.3 Bioaccumulative potential

Components:

octane

540-84-1:

- Partition coefficient: n-octanol/water : log Pow: 5,15

ethyl acetate

141-78-6:

- Bioaccumulation : Bioconcentration factor (BCF): 3,2
- Partition coefficient: n-octanol/water : log Pow: 0,73

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

12.4 Mobility in soil

Components:

octane

540-84-1:

Distribution among environmental compartments : Medium:Soil
Koc: 16000Remarks: immobile

ethyl acetate

141-78-6:

Distribution among environmental compartments : Koc: 59Remarks: Highly mobile in soils

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging : Empty remaining contents.
Empty pressure vessels should be returned to the supplier.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : European Waste Catalogue
16 05 04*
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

SECTION 14: Transport information

14.1 UN number

ADR : 1950
IMDG : 1950
IATA : 1950

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

14.2 Proper shipping name

ADR : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class

ADR : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)
IMDG
Labels : 2.1
EmS Number : F-D, S-U
IATA
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Labels : 2.1

14.5 Environmental hazards

ADR
Environmentally hazardous : yes

IMDG
Marine pollutant : yes
IATA
Environmentally hazardous : no

14.6 Special precautions for user

For personal protection see section 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

		Quantity 1	Quantity 2
8	Extremely flammable	10 000067	50 000067
9a	Dangerous for the environment	100 000067	200 000067
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.			
P3a	FLAMMABLE AEROSOLS	150 000067	500 000067
E1	ENVIRONMENTAL	100 000067	200 000067

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

HAZARDS

34 Petroleum products: (a) 2.500 000067 25.000 000067
gasolines and naphthas, (b)
kerosenes (including jet fuels),
(c) gas oils (including diesel
fuels, home heating oils and
gas oil blending streams),(d)
heavy fuel oils

TA Luft List (Germany) : Total dust: Not applicable
: Inorganic substances in powdered form: Not applicable
: Inorganic substances in vapour or gaseous form: Not applicable
: Organic Substances: Not applicable
: Carcinogenic substances: Not applicable
: Mutagenic: Not applicable
: Toxic to reproduction: Not applicable

Volatile organic compounds (VOC) content : Percent volatile: 35,6 %
233,54 g/l
VOC content excluding water

Volatile organic compounds (VOC) content : Percent volatile: 35,6 %
233,54 g/l
VOC content valid only for coating materials used on wood surfaces

according to Detergents Regulation EC 648/2004 : >=30% Aliphatic hydrocarbons

Diğer kurallar : 26 Aralık 2008 tarihli,27092 mükerrer sayılı," T.C. Çevre ve Orman Bakanlığı Tehlikeli Maddeler ve Müstahzarlara İlişkin Güvenlik Bilgi Formlarının Hazırlanması ve Dağıtılması Hakkında Yönetmeliği " ne uygun düzenlenmiştir.
26 Aralık 2008 27092 (mükerrer) sayılı Tehlikeli Maddelerin ve Müstahzarların Sınıflandırılması Ambalajlanması ve Etiketlenmesi Hakkında Yönetmelik hükümlerine göre hazırlanmıştır.

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

EUH066 Repeated exposure may cause skin dryness or cracking.
H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Further information

BUF AQUA STOP 250ML

WM 0900127

Order number: 0900127

Version 3.0

Revision Date 03.05.2017

Print Date 17.07.2017

Classification procedure:	H222, H229	On basis of test data.
	H315	Calculation method
	H336	Calculation method
	H400	Calculation method
	H410	Calculation method

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

50000003830