according to Regulation (EC) No. 1907/2006



MORELLO LEDERFARBE HELLBRAUN 40 ML

WM 0900947 Order number:

Version 1 Revision Date 28.09.2010 Print Date 27.01.2011

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product information

Trade name : MORELLO LEDERFARBE HELLBRAUN 40 ML

Identification number : 63395

Use of the Sub- : Care product / Polish

stance/Mixture

Company : Bergal, Nico & Solitaire Vertr. GmbH

Rheinallee 96 55120 Mainz

: +49(0)6131-19240

Telephone : +49613196404 Telefax : +4961319642515

E-mail address Responsi-

ble/issuing person

2. HAZARDS IDENTIFICATION

Feedback (alanhana

Emergency telephone num-

ber

: Produktsicherheit@werner-mertz.com

Risk advice to man and the environment

Highly flammable. Irritating to eyes.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Alcoholic solution

Hazardous components

Chemical Name	CAS-No.	EC-No. / Registration number	Classification	Concentration [%]
acetone	67-64-1	200-662-2	F; R11 Xi; R36 R66 R67	>= 40 - < 50
ethanol	64-17-5	200-578-6	F; R11	>= 25 - < 40

For the full text of the R-phrases mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

General advice : Move out of dangerous area. Consult a physician. Show this

safety data sheet to the doctor in attendance.

according to Regulation (EC) No. 1907/2006



MORELLO LEDERFARBE HELLBRAUN 40 ML

WM 0900947 Order number:

Version 1 Revision Date 28.09.2010 Print Date 27.01.2011

Inhalation : Move to fresh air. Consult a physician after significant expo-

sure.

Skin contact : Take off contaminated clothing and shoes immediately. Wash

off with soap and plenty of water. If symptoms persist, call a

physician.

Eye contact : Immediately flush eye(s) with plenty of water. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes.

Ingestion : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious per-

son. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry chemical

Alcohol-resistant foam Carbon dioxide (CO2)

Specific hazards during fire

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective equipment

for fire-fighters

Further information

: In the event of fire, wear self-contained breathing apparatus.

: Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Use personal protective equipment. Ensure adequate ventila-

tion. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive

concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so.

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

according to Regulation (EC) No. 1907/2006



MORELLO LEDERFARBE HELLBRAUN 40 ML

WM 0900947 Order number:

Version 1 Revision Date 28.09.2010 Print Date 27.01.2011

7. HANDLING AND STORAGE

Handling

Advice on safe handling : Avoid contact with skin and eyes. For personal protection see

section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Container may be opened only under ex-

haust ventilation hood.

Advice on protection against

fire and explosion

: Avoid formation of aerosol. Keep away from sources of igni-

tion - No smoking. Take measures to prevent the build up of electrostatic charge.

Storage

Requirements for storage

areas and containers

: No smoking. Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leak-

age. Electrical installations / working materials must comply with the technological safety standards. Store at room tem-

perature in the original container.

Other data : No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control pa- rameters	Update	Basis
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000-06-16	2000/39/EC
Further in- formation	: Indicative	Э			

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

Hand protection : Solvent-resistant gloves The selected protective gloves have

to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Before removing gloves

clean them with soap and water.

according to Regulation (EC) No. 1907/2006



MORELLO LEDERFARBE HELLBRAUN 40 ML

WM 0900947 Order number:

Version 1 Revision Date 28.09.2010 Print Date 27.01.2011

Eye protection : Eye wash bottle with pure water Tightly fitting safety goggles

Skin and body protection : impervious clothing Choose body protection according to the

amount and concentration of the dangerous substance at the

work place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form : liquid

Colour : light brown

Odour : characteristic

Safety data

Flash point : ca. -13,8 °C

Boiling point/boiling range : > 36 °C

Density : ca. 0,855 g/cm3

Water solubility : dispersible

10. STABILITY AND REACTIVITY

Conditions to avoid : Heat, flames and sparks.

Thermal decomposition : no data available

Hazardous reactions : Vapours may form explosive mixture with air.

: Stability:

No decomposition if used as directed.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

acetone : LD50 rat

Dose: 5.800 mg/kg

according to Regulation (EC) No. 1907/2006



MORELLO LEDERFARBE HELLBRAUN 40 ML

WM 0900947 Order number:

Version 1 Revision Date 28.09.2010 Print Date 27.01.2011

ethanol : LD50 rat

Dose: 6.200 mg/kg

LD50 mouse

Dose: 7.800 mg/kg

LD50 guinea pig Dose: 5.600 mg/kg

LD50 dog

Dose: 5.500 mg/kg

LD50 cat

Dose: 6.000 mg/kg

Acute inhalation toxicity

acetone : LC50 rat

Dose: 101 mg/l, 5 h

Acute dermal toxicity

acetone : LD50 rat

Dose: 20.000 mg/kg

LD50 rabbit

Dose: 20.000 mg/kg

LD50 guinea pig Dose: > 7.400 mg/kg

ethanol : LD50 rabbit

Dose: 20.000 mg/kg

Skin irritation : May cause skin irritation in susceptible persons.

Eye irritation : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Sensitisation : no data available

Further information : Concentrations substantially above the TLV value may cause

narcotic effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Solvents

may degrease the skin.

according to Regulation (EC) No. 1907/2006



MORELLO LEDERFARBE HELLBRAUN 40 ML

WM 0900947 Order number:

Version 1 Revision Date 28.09.2010 Print Date 27.01.2011

12. ECOLOGICAL INFORMATION

Biodegradability

acetone : Result: Readily biodegradable.

91 %

ethanol : Result: Readily biodegradable.

94 %

Method: OECD Test Guideline 301

Bioaccumulation

acetone : Bioconcentration factor (BCF): 1

Remarks:

Does not bioaccumulate.

Toxicity to fish

acetone : LC50

Species: Lepomis macrochirus (Bluegill sunfish)

Dose: 8.300,00 mg/l Exposure time: 96 h

ethanol : LC50

Species: Oncorhynchus mykiss (rainbow trout)

Dose: 13,00 g/l Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates.

acetone : Immobilization

EC50

Species: Daphnia magna (Water flea)

Dose: 6.100,00 mg/l Exposure time: 48 h

ethanol : EC50

Species: Daphnia magna (Water flea) Dose: 9.268,00 - 14.221,00 mg/l

Exposure time: 48 h

Toxicity to algae

acetone : static test

EC50

Species: Pseudokirchneriella subcapitata (green algae)

Dose: 7.000,00 mg/l Exposure time: 120 h

Distribution among environmental compartments

according to Regulation (EC) No. 1907/2006



MORELLO LEDERFARBE HELLBRAUN 40 ML

WM 0900947 Order number:

Revision Date 28.09.2010 Print Date 27.01.2011 Version 1

ethanol : Medium: Soil

Remarks:

Highly mobile in soils

Additional advice Environmental fate and pathways

Further information on ecology

Chemical Oxygen Demand (COD)

acetone : 2.070 mg/g

Additional ecological informa: There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Product : Do not dispose of waste into sewer.Do not contaminate

> ponds, waterways or ditches with chemical or used container. Offer surplus and non-recyclable solutions to a li-

censed disposal company.

: Empty remaining contents. Dispose of as unused product. Do Contaminated packaging

not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

Waste Code : European Waste Catalogue

200127

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with

the waste disposal authorities.

14. TRANSPORT INFORMATION

ADR/RID

UN number : 1993

Description of the goods : FLAMMABLE LIQUID, N.O.S.

(acetone; ethanol)

: 3 Class Packing group : 11 Classification Code : F1 Hazard identification No 33 Labels 3

IMDG

UN number

Description of the goods : FLAMMABLE LIQUID, N.O.S.

(Acetone; Ethanol)

Class : 3 : II Packaging group Labels : 3

according to Regulation (EC) No. 1907/2006



MORELLO LEDERFARBE HELLBRAUN 40 ML

WM 0900947 Order number:

Version 1 Revision Date 28.09.2010 Print Date 27.01.2011

EmS Number : F-E Marine pollutant : no

15. REGULATORY INFORMATION

Labelling according to EC Directives

1999/45/EC

Symbol(s)

F

Xi



Highly flammable

R-phrase(s)

R11 : Highly flammable. R36 : Irritating to eyes.

R66 : Repeated exposure may cause skin dryness or cracking.

R67 : Vapours may cause drowsiness and dizziness.

S-phrase(s)

S 2 : Keep out of the reach of children.

S16 : Keep away from sources of ignition - No smoking.

S23Do not breathe vapour.S25Avoid contact with eyes.

S35 : This material and its container must be disposed of in a safe

way.

S46 : If swallowed, seek medical advice immediately and show this

container or label.

National legislation

Major Accident Hazard Leg-

islation

: 96/82/EC Update: 2003

Highly flammable

7b

Quantity 1: 5.000 000067 Quantity 2: 50.000 000067

Volatile organic compounds

(VOC) content

: Percent volatile: 79,58 %

698,81 g/l

VOC content excluding water

Volatile organic compounds

(VOC) content

: Percent volatile: 79,58 %

680,42 g/l

VOC content valid only for coating materials used on wood

surfaces

according to Regulation (EC) No. 1907/2006



MORELLO LEDERFARBE HELLBRAUN 40 ML

WM 0900947 Order number:

Version 1 Revision Date 28.09.2010 Print Date 27.01.2011

16. OTHER INFORMATION

Full text of R-phrases referred to under sections 2 and 3

R11 Highly flammable. R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Contact person : Product development / product safety

500000001116