Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E
Date of print: 22.03.2018 Seite **1** von **10**



Safety data sheet

1. Substance/preparation and company identification

Trade name:

ASTI-S B-Komp

Application of the substance/ the preparation:

Polyurethane component

BFII

Kunststoffproduktions- und Handelsgesellschaft mbH

Lehmkuhlenweg 25

D- 31224 Peine

Telefon: +49 (0)5171/70 99-0 Telefax: +49 (0)5171/7099-29 E-Mail: service@beil-peine.de

Information in case of emergency:

Giftzentrale Göttingen Tel.: +49 (0)551/19240 Telefax: +49 (0)551/3831881

2. Hazards Identification

2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]Label elements

Acute Tox. 4 (Inhalation - vapour)

Eye Dam./Irrit. 2 Skin Corr./Irrit. 2

STOT SE 3 (irritating to respiratory system)

Skin Sens. 1 Resp. Sens. 1

Carc. 2

STOT RE 2 (Inhalation - vapour)

H315, H317, H319, H332, H334, H335, H351, H373

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

Globally Harmonized System, EU (GHS)

Pictogram:





Signal Word:

Danger

Hazard Statement:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Kunststoffproduktions- und

Handelsgesellschaft mbH

Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E
Date of print: 22.03.2018 Seite **2** von **10**



H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated inhalative exposure.

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 Incase of inadequate ventilation wear respiratory protection.

Precautionary Statements (Response):

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Labeling of special preparations (GHS):

Contains isocyanates. May produce an allergic reaction.

According to Regulation (EC) No 1272/2008 [CLP]

Hazard determining component(s) for labelling:

Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

Preparation based on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI) Hazardous ingredients (GHS) according to Regulation (EC) No. 1272/2008

Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Content (W M): >= 10 % - <= 90 % Acute Tox. 4 (Inhalation - vapour)

CAS Number: 9016-87-9 Eye Dam./Irrit. 2 Skin Corr./Irrit. 2

STOT SE 3 (irr. to respiratory syst.)

Skin Sens. 1 Resp. Sens. 1

Carc. 2

STOT RE 2 (Inhalation - vapour)

H315, H317, H319, H332, H334, H335, H351, H373

EUH204

For the classifications not written out in full in this section, including the indication of danger, the hazard symbols, the R phrases, and the hazard statements, the full text is listed in section 16.

4. First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

After contact with skin, wash immediately with plenty of water. Consult a doctor if skin irritation persists.

Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E Date of print: 22.03.2018 Seite **3** von **10**



On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink plenty of water, do not induce vomiting, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: tightness in the chest, coughing, difficulty breathing

Hazards: Symptoms can appear later.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote, administer corticosteroid dose aerosol to prevent pulmonary odema.

5. Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: dry powder, carbon dioxide, alcohol-resistant foam, water spray Unsuitable extinguishing media for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

Carbon dioxide, carbon monoxide, hydrogen cyanide; hydrocyanic acid, nitrogen oxides, isocyanate. The substances/groups of substances mentioned can be released in case of fire.

5.3. Advice for fire-fighters

Special protective equipment:

Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures see, section 8. Ensure adequate ventilation. Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not empty into drains. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder). Dispose of absorbed material in accordance with regulations. Neutralize with a solution of 5 - 10 % Sodium carbonate, 0,2 - 2 % detergents and 90 - 95 % water. 6.4. Reference to other sections Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

7. Handling and Storage

7.1. Precautions for safe handling

Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated, and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. Clean up contamination as soon as they occur. Provide basic employee training to prevent/minimize exposures. Products freshly manufactured from isocyanates can contain incompletely reacted isocyanates and other dangerous substances, e.g. primary aromatic amines. Industrial cleaning with aprotic polar solvents (meeting the IUPAC definition) may lead to formation of hazardous primary aromatic amine (>0,1%). See Section 11.

Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E
Date of print: 22.03.2018 Seite **4** von **10**



Protection against fire and explosion: No special precautions necessary.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from water. Segregate from foods and animal feeds. Segregate from acids and bases. Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), tinned carbon steel (Tinplate), Stainless steel 1.4301 (V2)

Storage stability:

Protect against moisture.

If moisture enters isocyanate containers, CO2 forms and pressure builds up.

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

8. Exposure Controls/Personal Protection

8.1. Control parameters

PNEC

No PNEC value available.

DNEL

No DNELs have been derived.

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Respiratory protection in case of vapour/aerosol release. (Combination filter EN 14387 A-P2)

Hand protection:

Chemical resistant protective gloves (EN 374)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6,

corresponding > 480 minutes of permeation time according to EN 374):

butyl rubber (butyl) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

chloroprene rubber (CR) - 0.5 mm coating thickness

Unsuitable materials

polyvinylchloride (PVC) - 0.7 mm coating thickness

Polyethylene-Laminate (PE laminate) - ca. 0.1 mm coating thickness

Suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (meeting the IUPAC definition):

butyl rubber (butyl) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

chloroprene rubber (CR) - 0.5 mm coating thickness

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

safety shoes (e.g. according to EN 20346)

General safety and hygiene measures

Do not breathe vapour/spray. With products freshly manufactured from isocyanates body protection and chemical resistant protective gloves is recommended. Wearing of closed work clothing is required additionally to the stated personal protection equipment. No eating, drinking, smoking or tobacco use at the place of work. Take off immediately all contaminated clothing. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form: liquid
Colour: brown
Odour: earthy, musty
Odour threshold: not applicable

Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E
Date of print: 22.03.2018 Seite **5** von **10**



pH value: not applicable

Boiling range: > 200 °C (1,013 mbar)

Flash point: > 200 °C
Evaporation rate: not applicable
Flammability: does not ignite
Lower explosion limit: not determined
Ignition temperature: > 530 °C

Vapour pressure: < 0.01 Pa (25 °C)
Density: 1.21 g/cm³ (20 °C)
Relative vapour density (air): not applicable

Solubility in water: Hydrolyzes to form water-insoluble compounds.

Partitioning coefficient

n-octanol/water (log Kow): not applicable Thermal decomposition: > 230 °C

Viscosity, dynamic: 110 mPa.s (25 °C) Explosion hazard: not explosive Fire promoting properties: not fire-propagating

9.2. Other information

Miscibility with water: Reacts with water.

Other Information: If necessary, information on other physical and chemical parameters is

indicated in this section.

10. Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid moisture.

Temperature: < 15 °C

10.5. Incompatible materials

Substances to avoid:

acids, alcohols, amines, water, alkalines

10.6. Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Virtually nontoxic after a single ingestion.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Of moderate toxicity after short-term inhalation.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Experimental/calculated data:

LC50 rat (by inhalation): approx. 0.493 mg/l 4 h

Telefon: +49 (0) 5171 70 99 0 Fax: +49 (0) 5171 70 99 29

Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E Date of print: 22.03.2018 Seite **6** von **10**



Irritation

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible. The substance may cause sensitization of the respiratory tract.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Assessment of sensitization:

The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:

The chemical structure does not suggest a specific alert for such an effect.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Assessment of mutagenicity:

The substance was mutagenic in various test systems with microorganisms and cell cultures; however, these results could not be confirmed in tests with mammals.

Carcinogenicity

Assessment of carcinogenicity:

A carcinogenic effect cannot safely be ruled out.

Industrial cleaning with aprotic polar solvents (meeting the IUPAC definition) may lead to formation of hazardous primary aromatic amine (>0,1%). Primary aromatic amines are chemicals that are regarded as potenttially carcinogenic for humans based on animal testing. Some of these chemicals are known human carcinogens. No adverse health effects are anticipated if recommended personal protective equipment and industrial hygiene practices are used.

Reproductive toxicity

Assessment of reproduction toxicity:

The chemical structure does not suggest a specific alert for such an effect.

Developmental toxicity

Assessment of teratogenicity:

The chemical structure does not suggest a specific alert for such an effect.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Assessment of teratogenicity:

Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated inhalation exposure may affect certain organs. Repeated exposure to the substance by dermal administration leads to effects similar to those found after single exposure. Repeated exposure

Handelsgesellschaft mbH

Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E
Date of print: 22.03.2018 Seite **7** von **10**



to the substance by oral administration leads to effects similar to those found after single exposure.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Assessment of repeated dose toxicity:

The substance may cause damage to the lung even after repeated inhalation of low doses, as shown in animal studies.

Aspiration hazard No aspiration hazard expected.

Other relevant toxicity information

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Toxicity to fish: LC0 (96 h) > 1,000 mg/l, Fish (other)

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Aquatic invertebrates: EC0 (24 h) > 500 mg/l, daphnia (other)

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Aquatic plants: EC0 (72 h) 1,640 mg/l, Scenedesmus subspicatus (OECD Guideline 201)

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O): Hydrolyzes to form water-insoluble compounds.

Experience shows this product to be inert and non-degradable.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Elimination information: < 10 % BOD of the ThOD (28 d) (OECD Guideline 302 C) (aerobic, activated sludge) Under test conditions no biodegradation observed.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential: Does not significantly accumulate in organisms.

Information on: Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)

Assessment bioaccumulation potential:

Does not significantly accumulate in organisms.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH):

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer.

12.7. Additional information

Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E
Date of print: 22.03.2018 Seite **8** von **10**



Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

Do not release untreated into natural waters. Do not allow to enter soil, waterways or waste water channels.

13. Disposal Considerations

13.1. Waste treatment methods

Incinerate in suitable incineration plant, observing local authority regulations.

Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).

Waste key: 08 05 01¤ waste isocyanates

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

This material and its container must be disposed of in a safe way.

14. Transport Information

Land transport

ADR Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Not applicable
Not applicable
Not applicable

Special precautions for user Not known

RID Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for user

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not known

Inland waterway transport

ADN Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for user

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not known

Transport in inland waterway vessel

Not evaluated **Sea transport**

IMDG Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for user

Not applicable
Not applicable
Not applicable
Not applicable
Not known

Air transport

IATA/ICAO Not classified as a dangerous good under transport regulations

Telefon:

+49 (0) 5171 70 99 0

+49 (0) 5171 70 99 29

UN number: Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Not applicable

Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E
Date of print: 22.03.2018 Seite **9** von **10**



Packing group: Not applicable Environmental hazards: Not applicable Special precautions for user Not known

14.1. UN number

See corresponding entries for "UN number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation: Not evaluated
Shipment approved: Not evaluated
Pollution name: Not evaluated
Pollution category: Not evaluated
Ship Type: Not evaluated

15. Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

If it is intended to use materials for the manufacture of consumer goods (e. g. products which will come into contact with foodstuffs or with the skin, toys) or medical products, national and international regulations have to be observed. Where no regulations exist, consumer goods or medical products must at least comply with European legislation. We recommend contacting our Sales and our Product Safety departments.

15.2. Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

16. Other Information

Full text of the classifications, including the indication of danger, the hazard symbols, the R phrases, and the hazard statements, if mentioned in section 2 or 3:

Acute Tox. Acute toxicity

Eye Dam./Irrit. Serious eye damage/eye irritation

Skin Corr./Irrit. Skin corrosion/irritation

STOT SE Specific target organ toxicity — single exposure

Skin Sens. Skin sensitization
Resp. Sens. Respiratory sensitization

Carc. Carcinogenicity

STOT RE Specific target organ toxicity — repeated exposure

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

Date / Revised: 07.03.2018

Product: ASTI-S B-Komp. Version 6.1 E
Date of print: 22.03.2018 Seite **10** von **10**



H334	May cause allergy or asthma symptoms or breathing difficulties if
	inhaled.
H335	May cause respiratory irritation.

H335 May cause respiratory irritation
H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated

inhalative exposure.

EUH Contains isocyanates. May produce an allergic reaction.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.