Date / Revised: 17.08.2015

Product: BKF Spachtel SL-plus Version: 1.1 E
Date of print: 17.08.2015 Page: 1 von 6



Safety data sheet

1. Substance/preparation and company identification

Trade name:

BKF Spachtel SL-plus

Application of the substance/ the preparation:

Putty

BEIL

Kunststoffproduktions- und Handelsgesellschaft mbH

Lehmkuhlenweg 25 D- 31224 Peine

Telefon: +49 (0)5171/70 99-0 Telefax: +49 (0)5171/7099-29 E-Mail: <u>service@beil-peine.de</u>

Information in case of emergency:

Giftzentrale Göttingen Tel.: +49 (0)551/19240 Telefax: +49 (0)551/3831881

2. Hazard identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT RE 1: H372; Eye Irrit. 2: H319; Flam. Liq. 3: H226;

Repr. 2: H361d; Skin Irrit. 2: H315

Most important adverse effects: Flammable liquid and vapour. Causes skin irritation. Causes

serious eye irritation.

Suspected of damaging the unborn child. Causes damage to organs [hearing organs] through prolonged or repeated

exposure.

2.2. Label elements Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H361d: Suspected of damaging the unborn child.

H372: Causes damage to organs [hearing organs] through

prolonged or repeated exposure.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard



Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Date / Revised: 17.08.2015

Product: BKF Spachtel SL-plus Version: 1.1 E Date of print: 17.08.2015 Page: **2** von **6**



P241: Use explosion-proof electrical/ventilating/lighting equipment.

P243: Take precautionary measures against static discharge.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. P332+313: If skin irritation occurs: Get medical

advice/attention.

P337+313: If eye irritation persists: Get medical

advice/attention.

P370+378: In case of fire: Use alcohol-resistant foam to

extinguish.

P403+235: Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture. PBT: This product is not identified as a PBT/vPvB substance.

3. Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

STYRENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-851-5	100-42-5	-	Flam. Liq. 3: H226; Repr. 2: H361d; Acute Tox. 4: H332; STOT RE 1: H372; Skin Irrit. 2: H315; Eye Irrit. 2: H319	10-30%

4. First-aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately

unless stuck to skin. Wash immediately with plenty of soap

and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

5. Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry

chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive

air-vapour mixture.

Date / Revised: 17.08.2015

Product: BKF Spachtel SL-plus Version: 1.1 E
Date of print: 17.08.2015 Page: 3 von 6



5.3. Advice for fire-fighters Advice for fire-fighters:

Wear self-contained breathing apparatus. Wear protective

clothing to prevent contact with skin and eyes.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify

the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the

escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage

using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled

salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce

sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

7. Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. U

Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread

of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly

closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Coated steel.

7.3. Specific end use(s)

Specific end use(s): No data available.

8. Exposure controls and personal protection

8.1. Control parameters Hazardous ingredients:

STYRENE

Workplace exposure limits:

Res	pirable	dust
-----	---------	------

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	86 mg/m ³	2	-	-

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and

electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Odour: Characteristic odour

Date / Revised: 17.08.2015

Product: BKF Spachtel SL-plus Version: 1.1 E

Date of print: 17.08.2015 Page: 4 von 6



Solubility in water: Slightly soluble
Also soluble in: Most organic solvents.

Viscosity: Highly viscous

Kinematic viscosity: n.V. Boiling point/range°C: 145 Melting point/range°C: n.V. Flammability limits %: lower: 1,1 upper: 8 Flash point °C: Part.coeff. n-octanol/water: 34 n v Autoflammability°C: 480 Vapour pressure: 7 mbar Relative density: 0,96 g/cm3 pH: n.v.

VOC g/l: 243

9.2. Other information

Other information: No data available.

10. Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage

conditions. Decomposition may occur on exposure to conditions or

Telefon:

+49 (0) 5171 70 99 0

+49 (0) 5171 70 99 29

materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

11. Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

STYRENE

IVN	MUS	LD 50	90	mg/kg
ORL	MUS	LD 50	316	mg/kg
ORL	RAT	LD 50	2650	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

12. Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Date / Revised: 17.08.2015

Product: BKF Spachtel SL-plus Version: 1.1 E
Date of print: 17.08.2015 Page: **5** von **6**



13. Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by

specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or

toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or

national regulations regarding disposal.

14. Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group:

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E Transport category: 3

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

16. Other information

Other information: This safety data sheet is prepared in accordance with

Commission Regulation (EU) No 453/2010.

Polyester resin for multi-component systems (base + hardener) must be declared with UN no. 3269 according to GGVS/ADR and IMDG-code.

* indicates text in the SDS which has changed since

the last revision.

Phrases used in s.2 and s.3:

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H361d: Suspected of damaging the unborn child. H372: Causes damage to organs <or state all organs

affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of

exposure cause the hazard>.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Date / Revised: 17.08.2015

Product: BKF Spachtel SL-plus Version: 1.1 E
Date of print: 17.08.2015 Page: **6** von **6**

The information contained here in is based on the present state of our knowledge and does not therefore guarantee certain properties. Recipients of our product must take responsibility for observing existing laws and regulations.