SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)

TRG LA INDUSTRIAL SUPER TINTA RAPIDA 118



Version: 5 Revision date: 26/06/2017 Page 1 of 12 Print date: 14/09/2017

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name:

TRG LA INDUSTRIAL SUPER TINTA RAPIDA 118

1.2 Relevant identified uses of the mixture and uses advised against.

To change colour in leather and synthetic leather. Only for change light colours to dark.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	TRG BESTNETS, S.L.
Address:	Sant Antoni Maria Claret, 6
City:	08271 Artés
Province:	BARCELONA - SPAIN
Telephone:	(+34) 93 830 64 42
Fax:	(+34) 93 830 64 43
E-mail:	www.trg-theone.com

1.4 Emergency telephone number: (+34) 93 830 64 42 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008: Eye Irrit. 2 : Causes serious eye irritation. Flam. Liq. 3 : Flammable liquid and vapour.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008: Pictograms:



Signal Word:

Warning

H statements: H226 H319

Flammable liquid and vapour. Causes serious eye irritation.

P statements:

Stateme	cincs.	
P210		Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280		Wear protective gloves/protective clothing/eye protection/face protection.
P305-	+P351+P3	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
easy	to do. Con	tinue rinsing.
P337-	+P313	If eye irritation persists: Get medical advice/attention.
P370-	+P378	In case of fire: Use extinguishing powder or CO2 for extinction.
P403-	+P235	Store in a well-ventilated place. Keep cool.
P501		Dispose of contents/container according to local regulations.

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.



Version: 5 Revision date: 26/06/2017

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification No 127	- Regulation (EC) 2/2008
Identifiers	Name	Concentrate	Classification	specific concentration limit
Index No: 603-016- 00-1 CAS No: 123-42-2 EC No: 204-626-7 Registration No: 01- 2119473975-21-XXXX	[1] 4-hydroxy-4-methylpentan-2-one,diacetone alcohol	10 - 50 %	Eye Irrit. 2, H319	Eye Irrit. 2, H319: C ≥ 10 %
Index No: 603-117- 00-0 CAS No: 67-63-0 EC No: 200-661-7 Registration No: 01- 2119457558-25-XXXX	[1] isopropanol,isopropyl alcohol,propan-2-ol	10 - 20 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 603-002- 00-5 CAS No: 64-17-5 EC No: 200-578-6 Registration No: 01- 2119457610-43-XXXX	[1] ethanol,ethyl alcohol	2.5 - 10 %	Flam. Liq. 2, H225	-
Index No: 601-021- 00-3 CAS No: 108-88-3 EC No: 203-625-9 Registration No: 01- 2119471310-51-XXXX	[1] toluene	0.1 - 3 %	Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Repr. 2, H361d *** - Skin Irrit. 2, H315 - STOT RE 2 *, H373 ** - STOT SE 3, H336	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

*,**,*** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

(in accordance with Regulation (EU) 2015/830)

TRG LA INDUSTRIAL SUPER TINTA RAPIDA 118



Version: 5 Revision date: 26/06/2017 Page 3 of 12 Print date: 14/09/2017

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO_2 . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes.For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

(in accordance with Regulation (EU) 2015/830)

TRG LA INDUSTRIAL SUPER TINTA RAPIDA 118



Version: 5 Revision date: 26/06/2017 Page 4 of 12 Print date: 14/09/2017

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks.For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s). Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
4-hydroxy-4-methylpentan-2-	123-42-2	United	Eight hours	50	241
one, diacetone alcohol	123-42-2	Kingdom [1]	Short term	75	362
isopropanol, isopropyl alcohol, propan-2-	67-63-0	United	Eight hours	400	999
ol	07-03-0	Kingdom [1]	Short term	500	1250
ethanol,ethyl alcohol	64-17-5	United	Eight hours	1000	1920
		Kingdom [1]	Short term		
	108-88-3	Union [2]	Eight hours	50 (skin)	192 (skin)
toluene			Short term	100 (skin)	384 (skin)
		United	Eight hours	50	191
		Kingdom [1]	Short term	100	384

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. [2] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
4-hydroxy-4-methylpentan-2-one,diacetone alcohol	DNEL	Inhalation, Long-term, Local effects	66,4
CAS No: 123-42-2	(Workers)		(mg/m ³)
EC No: 204-626-7	DNEL	Inhalation, Long-term, Systemic effects	66,4
LC NO. 204-020-7	(Workers)		(mg/m ³)
	DNEL	Inhalation, Long-term, Systemic effects	500
	(Workers)		(mg/m ³)
	DNEL (General	Inhalation, Long-term, Systemic effects	89
	population)		(mg/m ³)
icontenanal icontenul alcohol atenan 2 al	DNEL	Dermal, Long-term, Systemic effects	888
isopropanol, isopropyl alcohol, propan-2-ol CAS No: 67-63-0	(Workers)		(mg/kg
EC No: 200-661-7			bw/day)
EC NO: 200-001-7	DNEL (General	Dermal, Long-term, Systemic effects	319
	population)		(mg/kg
	,		bw/day)
	DNEL (General	Oral, Long-term, Systemic effects	26 (mg/kg
	population)		bw/day)

(in accordance with Regulation (EU) 2015/830)

TRG LA INDUSTRIAL SUPER TINTA RAPIDA 118



Version: 5

Revision date: 26/06/2017

Page 5 of 12 Print date: 14/09/2017

ethanol,ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	DNEL (Workers)	Inhalation, Long-term, Systemic effects	950 (mg/m³)
	DNEL (Workers)	Inhalation, Long-term, Local effects	192 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	192 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Systemic effects	384 (mg/m ³)
toluene	DNEL (General population)	Inhalation, Acute, Systemic effects	226 (mg/m ³)
CAS No: 108-88-3 EC No: 203-625-9	DNEL (Workers)	Inhalation, Acute, Local effects	384 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Local effects	226 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	384 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	226 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	8,13 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
	aqua (freshwater)	140,9 (mg/L)
	aqua (marine water)	140,9 (mg/L)
	aqua (intermittent releases)	140,9 (mg/L)
	sediment (freshwater)	552 (mg/kg
icopropagal icopropyl alcohol propag 2 ol		sediment dw)
isopropanol, isopropyl alcohol, propan-2-ol CAS No: 67-63-0	sediment (marine water)	552 (mg/kg
EC No: 200-661-7		sediment dw)
EC NO. 200 001 /	Soil	28 (mg/kg
		soil dw)
	PNEC STP	2251 (mg/L)
	PNEC oral (Hazard for predators)	160 (mg/kg
		food)
	Fresh water	0,96 (mg/L)
	Marine water	0,79 (mg/L)
ethanol, ethyl alcohol	aqua (intermittent releases)	2,75 (mg/L)
CAS No: 64-17-5	Soil	0,63 (mg/kg
EC No: 200-578-6		soil dw)
	sediment (freshwater)	3,6 (mg/kg
		sediment dw)
	aqua (freshwater)	0,68 (mg/L)
	aqua (marine water)	0,68 (mg/L)
toluene	aqua (intermittent releases)	0,68 (mg/L)
CAS No: 108-88-3 EC No: 203-625-9	PNEC STP	13,61 (mg/L)
	sediment (freshwater)	16,39 (mg/kg
		sediment dw)
	sediment (marine water)	16,39 (mg/kg
		sediment dw)



Version: 5 Revision date: 26/06/2017

Page 6 of 12 Print date: 14/09/2017

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	To change colour in leather and synthetic leather. Only for change light colours to dark.
Breathing protecti	on:
If the recommended	technical measures are observed, no individual protection equipment is necessary.
Hand protection:	
	dled correctly, no individual protection equipment is necessary.
Eye protection:	
PPE: Characteristics:	Face shield. «CE» marking, category II. Face and eye protector against splashing liquid.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.
Skin protection:	
PPE: Characteristics:	Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE: Characteristics:	Anti-static safety footwear. «CE» marking, category II.
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346
Maintenance: Observations:	The footwear should be checked regularly The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour and colour Colour: N.A./N.A. Odour:N.A./N.A. Odour threshold:N.A./N.A. pH:N.A./N.A. Melting point:N.A./N.A. Boiling Point: N.A./N.A. Flash point: 32 °C Evaporation rate: N.A./N.A. Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:N.A./N.A. Relative density:N.A./N.A. Solubility:N.A./N.A.



Version: 5 Revision date: 26/06/2017

Page 7 of 12 Print date: 14/09/2017

Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A. Partition coefficient (n-octanol/water): N.A./N.A. Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A. Viscosity: N.A./N.A. Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A. N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A. Blink: N.A./N.A. Kinematic viscosity: N.A./N.A. N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.

- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

10.5 Incompatible materials.

- Avoid the following materials:
- Explosives materials.
- Toxic materials.
- Oxidizing materials.

10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation; Based on available data, the classification criteria are not met.

c) serious eye damage/irritation; Product classified: Eye irritation, Category 2: Causes serious eye irritation.



Version: 5 Revision date: 26/06/2017

Page 8 of 12 Print date: 14/09/2017

d) respiratory or skin sensitisation; Not conclusive data for classification.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Based on available data, the classification criteria are not met.

h) STOT-single exposure; Based on available data, the classification criteria are not met.

i) STOT-repeated exposure; Based on available data, the classification criteria are not met.

j) aspiration hazard; Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity				
Name	Туре	Test	Kind	Value	
	Fish	Toxicities o (Pimephale	f Organic Chemicals s promelas), Volume	31,7 mg/l (96 h) [1] nd D.J. Call 1990. Acute to Fathead Minnows 5. Ctr.for Lake Superior n-Superior, Superior, WI :332	
toluene	Aquatic invertebrates	LC50 Crustacean 92 mg/l (48 h) [1] [1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to Daphnia magna and Artemia. Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p			
CAS No: 108-88-3 EC No: 203-625-9	Aquatic plants	M.L.Tosato of Aquatic		,	

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
Name	Log Pow	BCF	NOECs	Level
4-hydroxy-4-methylpentan-2-one,diacetone alcohol	-0,34	-	-	Very low

(in accordance with Regulation (EU) 2015/830)

TRG LA INDUSTRIAL SUPER TINTA RAPIDA 118



Version: 5

Revision date: 26/06/2017

Page 9 of 12 Print date: 14/09/2017

N. CAS: 123-42-2	EC No: 204-626-7				
isopropanol, isopropyl alco	isopropanol,isopropyl alcohol,propan-2-ol				
N. CAS: 67-63-0	EC No: 200-661-7	0,05	-	-	Very low
ethanol, ethyl alcohol		-0,3	_	_	Very low
N. CAS: 64-17-5	EC No: 200-578-6	-0,5	_	-	Very IOW
toluene		2,73	_	_	Low
N. CAS: 108-88-3	EC No: 203-625-9	2,75			LOW

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.



Version: 5 Revision date: 26/06/2017

Page 10 of 12 Print date: 14/09/2017

14.1 UN number. UN No: UN1993

118

14.2 UN proper shipping name.

Description: ADR: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ISOPROPANOL, ISOPROPYL ALCOHOL, PROPAN-2-OL / ETHANOL, ETHYL ALCOHOL), 3, PG II, (D/E) IMDG: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ISOPROPANOL, ISOPROPYL ALCOHOL, PROPAN-2-OL / ETHANOL, ETHYL ALCOHOL), 3, PG II ICAO: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ISOPROPANOL, ISOPROPYL ALCOHOL, PROPAN-2-OL / ETHANOL, ETHYL ALCOHOL), 3, PG II

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 3



Hazard number: 33 ADR LQ: 1 L IMDG LQ: 1 L ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

(in accordance with Regulation (EU) 2015/830)

TRG LA INDUSTRIAL SUPER TINTA RAPIDA 118



Page 11 of 12 Print date: 14/09/2017

Version: 5 Revision date: 26/06/2017

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Classification codes:

Asp. Tox. 1 : Aspiration toxicity, Category 1 Eye Irrit. 2 : Eye irritation, Category 2 Flam. Liq. 2 : Flammable liquid, Category 2 Flam. Liq. 3 : Flammable liquid, Category 3 Repr. 2 : Reproductive toxicant, Category 2 Skin Irrit. 2 : Skin irritant, Category 2 STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Sections changed compared with the previous version:

1,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Risk classification system NFPA 704:



Health hazard: 1 (Slightly Hazardous) Flammability: 3 (Below 100°F) Reactivity: 0 (Stable)

Abbreviations and acronyms used:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- Log Pow: Logarithm of the partition octanol-water.
- NOEC: No observed effect concentration.
- PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.



Version: 5 Revision date: 26/06/2017

Page 12 of 12 Print date: 14/09/2017

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.